


Day&Night IR Cameras



OSD Control Board



OSD




Digital Noise Reduction




PROFESSIONAL STANDALONE DVR



PTZ Control



IR Remote Control



HDMI 1080



CMS



iPhone & Android Application



IR Speed Dome camera

ST DIR36W

- 1/4" Exview HAD CCD
- Up to 540TVL /0.01 Lux
- IR distance: 120 ~150 meters
- 36x optical & 12x digital zoom lens
- Pan/Tilt: 360°/90°
- With Scan, Pattern, Preset
- 3D DNR, RS-485 (optional), Day & Night
- DC12V, IP66



IR Speed Dome camera

ST DIR28W

- 1/4" Exview HAD CCD
- Up to 550TVL /0.01 Lux
- IR distance: 120 ~150 meters
- 26x optical & 12x digital zoom lens
- Pan/Tilt: 360°/90°
- With Scan, Pattern, Preset
- 3D DNR, RS-485 (optional), Day & Night
- DC12V, IP66



Waterproof Dot Matrix Dome camera

ST ID48/O

- 1/3" SONY super HAD CCD
- Up to 650TVL / 0 Lux IR ON
- IR distance: 35 meters
- 6 mm fixed lens(3.6~8 mm optional)
- OSD menu, 3D DNR, DWDR, RS-485 (optional), HBLIC, Smart IR, Mirror, MD
- DC12V, IP66



Waterproof Dot Matrix Dome camera

ST ID47/O

- 1/3" SONY super HAD CCD
- Up to 600TVL / 0 Lux IR ON
- IR distance: 35 meters
- 6 mm fixed lens(3.6~8 mm optional)
- OSD menu, DWDR, 2D DNR, RS-485 (Optional), MD, BLC, AGC
- DC12V, IP66



Waterproof IR bullet camera

ST IR87/O

- 1/3" SONY super HAD CCD
- Up to 650TVL / 0 Lux IR ON
- IR distance: 50~60 meters
- 3.5~8 mm fixed lens
- OSD menu, 3D DNR, DWDR, RS-485 (Optional), HBLIC, Smart IR, Mirror, MD
- DC12V, IP66



Waterproof IR bullet camera

ST IR86/O

- 1/3" SONY super HAD CCD
- Up to 600TVL / 0 Lux IR ON
- IR distance: 50~60 meters
- 3.5~8 mm fixed lens
- OSD menu, DWDR, 2D DNR, RS-485 (Optional), MD, BLC, AGC
- DC12V, IP66



Box camera

ST IF14/O

- 1/3" SONY super HAD CCD
- Up to 650TVL
- Optional CS Mount lens
- OSD menu, 3D DNR, DWDR, RS-485 (optional), HBLIC, Smart IR, Mirror, MD
- DC12V



Box camera

ST IF13/O

- 1/3" SONY super HAD CCD
- Up to 600TVL
- Optional CS Mount lens
- OSD menu, DWDR, 2D DNR, RS-485 (Optional), MD, BLC, AGC
- DC12V



16 Channel CIF Real Time Recording

ST 5016L

- 16 CH VIDEO 2 CH AUDIO 480 Fps
- All channels CIF Video Recording
- playback 16ch CIF Simultaneously at 6 fps/ch
- 1 SATA Interfaces (Max support 2TB) - Voice Talk
- 10M/100M-TCP/IP - PPPoE/DHCP / DDNS / Mobile
- 1 xVGA Video - 1xBNC - 2xUSB - 64 Ch CMS
- 4/1 Alarm In/out - RS - 485 / IR Remote



16 Channel Full D1 Real Time Recording

ST 6016H

- 16 CH VIDEO 2 CH AUDIO 480 Fps
- All channels D1 Video Recording
- playback 16ch D1 at 6 fps/ch. Max 4ch D1 25fps
- 2 SATA Interfaces (Max support 4TB) - Voice Talk
- 100M/1000M-TCP/IP - PPPoE/DHCP / DDNS / Mobile
- 1 xVGA Video - 1xBNC - 2xUSB - 64 Ch CMS
- 4/1 Alarm In/out - RS - 485 / IR Remote



8 Channel CIF Real Time Recording

ST 5008L

- 8 CH VIDEO 2 CH AUDIO 440 Fps
- 1 Ch real D1 Adjustable, Other ch CIF Video
- playback 8ch CIF Simultaneously at 12 fps/ch.
- 1 SATA Interfaces (Max support 2TB) - Voice Talk
- 10M/100M-TCP/IP - PPPoE/DHCP / DDNS / Mobile
- 1 xVGA Video - 1xBNC - 2xUSB - 64 Ch CMS
- 4/1 Alarm In/out - RS - 485 / IR Remote



8 Channel Full D1 Real Time Recording

ST 6008H

- 8 CH VIDEO 2 CH AUDIO 240 Fps
- All channels D1 Video Recording
- playback 8ch D1 at 6 fps/ch. Max 4ch D1 25fps
- 2 SATA Interfaces (Max support 4TB) - Voice Talk
- HDMI (with audio): 1920 x 1080
- 1 xVGA Video - 1xBNC - 2xUSB - 64 Ch CMS
- 4/1 Alarm In/out - RS - 485 / IR Remote



4 Channel CIF Real Time Recording

ST 5004L

- 4 CH VIDEO 2 CH AUDIO 120 Fps
- 1 Ch Real D1 Adjustable, Other ch CIF Video
- playback 4ch CIF or 1ch D1 real time + 3ch CIF
- 1 SATA Interfaces (Max support 2TB) - Voice Talk
- 10M/100M-TCP/IP - PPPoE/DHCP / DDNS / Mobile
- 1 xVGA Video - 1xBNC - 2xUSB - 64 Ch CMS
- 4/1 Alarm In/out - RS - 485 / IR Remote



4 Channel Full D1 Real Time Recording

ST 6004H

- 4 CH VIDEO 2 CH AUDIO 120 Fps
- All channels D1 Video Recording
- playback 4ch D1 Simultaneously at 6 fps/ch
- 1 SATA Interfaces (Max support 2TB) - Voice Talk
- 10M/100M-TCP/IP - PPPoE/DHCP / DDNS / Mobile
- 1 xVGA Video - 1xBNC - 2xUSB - 64 Ch CMS
- 4/1 Alarm In/out - RS - 485 / IR Remote



32 Channel CIF Real Time Recording

ST 5032L

- 32 CH VIDEO 4 CH AUDIO 960 Fps
- All channels CIF Video Recording
- playback 4ch CIF Simultaneously
- 2 SATA Interfaces (Max support 4TB) - Voice Talk
- 10M/100M-TCP/IP - PPPoE/DHCP / DDNS / Mobile
- 1 xVGA Video - 1xBNC - 2xUSB - 64 Ch CMS
- 4/1 Alarm In/out - RS - 485 / IR Remote



24 Channel CIF Real Time Recording

ST 5024L

- 24 CH VIDEO 2 CH AUDIO 720 Fps
- All channels CIF Video Recording
- playback 4ch CIF Simultaneously
- 2 SATA Interfaces (Max support 4TB) - Voice Talk
- 10M/100M-TCP/IP - PPPoE/DHCP / DDNS / Mobile
- 1 xVGA Video - 1xBNC - 2xUSB - 64 Ch CMS
- 4/1 Alarm In/out - RS - 485 / IR Remote

professional Manufacturer of CCTV Product



2012 Version.2

SAYO.TECH

SAYO.TECH ELECTRONICS GROUP
Website: www.sayo-tech.co.kr
Email: info@sayotech.com
Email: support@sayotech.com

Waterproof IR Bullet Camera



OSD Control Board



OSD



Digital Noise Reduction



Waterproof IR Bullet Camera



OSD Control Board



OSD



Digital Noise Reduction



Waterproof IR Dome Camera




OSD Control Board



OSD



Digital Noise Reduction





ST IR97/O

- 1/3" SONY super HAD CCD
- Up to 650TVL/ 0 Lux IR ON
- IR distance: 50~60 meters
- 2.8~12 mm fixed lens(4~9 mm, 9~22 mm optional)
- OSD menu,3D DNR,DWDR,RS-485 (optional), HBLC, Smart IR, Mirror,MD,DSS
- DC12V , IP66

Long Range IR bullet camera



ST IR93/O

- 1/3" SONY super HAD CCD
- Up to 650TVL/ 0 Lux IR ON
- IR distance: 50~60 meters
- 2.8~12 mm varifocal lens
- OSD menu,3D DNR,DWDR,RS-485 (optional), HBLC, Smart IR, Mirror,MD,DSS
- DC12V , IP66

Long Range IR bullet camera



ST IR77/O

- 1/3" SONY super HAD CCD
- Up to 650TVL/ 0 Lux IR ON
- IR distance: 30 meters
- 2.8~12 mm varifocal lens
- OSD menu,3D DNR,DWDR,RS-485 (optional), HBLC, Smart IR, Mirror,MD,DSS
- DC12V , IP66

Mid Range IR bullet camera



ST IR73/O

- 1/3" SONY super HAD CCD
- Up to 650TVL/ 0 Lux IR ON
- IR distance: 25~30 meters
- 2.8~12 mm varifocal lens
- OSD menu,3D DNR,DWDR,RS-485 (optional), HBLC, Smart IR, Mirror,MD,DSS
- DC12V , IP66

Mid Range IR bullet camera



ST ID68/O

- 1/3" SONY super HAD CCD
- Up to 650TVL/ 0 Lux IR ON
- IR distance: 50~60 meters
- 2.8~12 mm varifocal lens
- OSD menu,3D DNR,DWDR,RS-485 (optional), HBLC, Smart IR, Mirror,MD,DSS
- DC12V , IP66

Waterproof IR Dome camera



ST ID45/O

- 1/3" SONY super HAD CCD
- Up to 650TVL/ 0 Lux IR ON
- IR distance: 15~20 meters
- 3.6 mm fixed lens
- OSD menu,3D DNR,DWDR,RS-485 (optional), HBLC, Smart IR, Mirror,MD,DSS
- DC 12V, IP66

Waterproof IR Dome camera



ST IR96/O

- 1/3" SONY super HAD CCD
- Up to 600TVL/ 0 Lux IR ON
- IR distance: 50~60 meters
- 2.8~12 mm fixed lens(4~9 mm, 9~2mm optional)
- OSD menu,3D DNR,DWDR,RS-485 (optional), HBLC, Smart IR, Mirror,MD
- DC12V , IP66

Long Range IR bullet camera



ST IR92/O

- 1/3" SONY super HAD CCD
- Up to 600TVL/ 0 Lux IR ON
- IR distance: 50~60 meters
- 2.8~12 mm varifocal lens
- AOSD menu,DWDR,2D DNR,RS-485 (optional), MD,BLC,AGC
- DC12V , IP66

Long Range IR bullet camera



ST IR76/O

- 1/3" SONY super HAD CCD
- Up to 600TVL/ 0 Lux IR ON
- IR distance: 30 meters
- 2.8~12 mm varifocal lens
- OSD menu,DWDR,2D DNR,RS-485 (optional), HBLC, Smart IR, Mirror,MD
- DC12V , IP66

Mid Range IR bullet camera



ST IR72/O

- 1/3" SONY super HAD CCD
- Up to 600TVL/ 0 Lux IR ON
- IR distance: 25~30 meters
- 2.8~12 mm varifocal lens
- OSD menu,DWDR,2D DNR,RS-485 (optional), MD,BLC,AGC
- DC12V , IP66

Mid Range IR bullet camera



ST ID67/O

- 1/3" SONY super HAD CCD
- Up to 540TVL/ 0 Lux IR ON
- IR distance: 50~60 meters
- 2.8~12 mm varifocal lens
- OSD menu,DWDR,2D DNR,RS-485 (optional), MD,BLC,AGC
- DC12V , IP66

Waterproof IR Dome camera



ST ID44/O

- 1/3" SONY super HAD CCD
- Up to 600TVL/ 0 Lux IR ON
- IR distance: 15~20 meters
- 3.6 mm fixed lens
- OSD menu,DWDR,2D DNR,RS-485 (optional), MD,BLC,AGC
- DC 12V, IP66

Waterproof IR Dome camera



ST IR95/O

- 1/3" SHARP CCD
- Up to 600TVL/ 0 Lux IR ON
- IR distance: 50~60 meters
- 2.8~12 mm fixed lens(4~9 mm, 9~22 mm optional)
- OSD menu,DWDR,2D DNR,RS-485 (optional), MD,BLC,AGC
- DC12V , IP66

Long Range IR bullet camera



ST IR91/O

- 1/3" SHARP CCD
- Up to 600TVL/ 0 Lux IR ON
- IR distance: 50~60 meters
- 2.8~12 mm varifocal lens
- OSD menu,DWDR,2D DNR,RS-485 (optional), MD,BLC,AGC
- DC12V , IP66

Long Range IR bullet camera



ST IR75/O

- 1/3" SHARP CCD
- Up to 600TVL/ 0 Lux IR ON
- IR distance: 30 meters
- 2.8~12 mm varifocal lens
- OSD menu,DWDR,2D DNR,RS-485 (optional), MD,BLC,AGC
- DC12V , IP66

Mid Range IR bullet camera



ST IR71/O

- 1/3" SHARP CCD
- Up to 600TVL/ 0 Lux IR ON
- IR distance: 25~30 meters
- 2.8~12 mm varifocal lens
- OSD menu,DWDR,2D DNR,RS-485 (optional), MD,BLC,AGC
- DC12V , IP66

Mid Range IR bullet camera



ST ID66/O

- 1/3" SHARP CCD
- Up to 600TVL/ 0 Lux IR ON
- IR distance: 50~60 meters
- 2.8~12 mm varifocal lens
- OSD menu,DWDR,2D DNR,RS-485 (optional), MD,BLC,AGC
- DC12V , IP66

Waterproof IR Dome camera



ST ID43/O

- 1/3" SHARP CCD
- Up to 600TVL/ 0 Lux IR ON
- IR distance: 15~20 meters
- 3.6 mm fixed lens
- OSD menu,DWDR,2D DNR,RS-485 (optional), MD,BLC,AGC
- DC12V , IP66

Waterproof IR Dome camera



ST IR63/O

- 1/3" SONY super HAD CCD
- Up to 650TVL/ 0 Lux IR ON
- IR distance: 60 meters
- 4 or 9 mm fixed lens
- OSD menu,3D DNR,DWDR,RS-485 (optional), HBLC, Smart IR, Mirror,MD,DSS
- DC12V , IP66

Long range IR bullet camera



ST IR62/O

- 1/3" SHARP CCD
- Up to 600TVL/ 0 Lux IR ON
- IR distance: 60 meters
- 4 or 9 mm fixed lens
- OSD menu,3D DNR,DWDR,2D DNR,RS-485 (optional), MD,BLC,AGC
- DC12V , IP66

Long Range IR bullet camera



ST IR52/O

- 1/3" SONY super HAD CCD
- Up to 650TVL/ 0 Lux IR ON
- IR distance: 15~20 meters
- 3.6 mm fixed lens
- OSD menu,3D DNR,DWDR,RS-485 (optional), HBLC, Smart IR, Mirror,MD,DSS
- DC12V , IP66

Low Range IR bullet camera



ST IR51/O

- 1/3" SHARP CCD
- Up to 600TVL/ 0 Lux IR ON
- IR distance: 15~20 meters
- 3.6 mm fixed lens
- OSD menu,DWDR,2D DNR,RS-485 (optional), MD,BLC,AGC
- DC12V , IP66

Low Range IR bullet camera



ST ID58/O

- 1/3" SONY super HAD CCD
- Up to 650TVL/ 0 Lux IR ON
- IR distance: 15~20 meters
- 3.6 mm fixed lens
- OSD menu,3D DNR,DWDR,RS-485 (optional), HBLC, Smart IR, Mirror,MD,DSS
- DC 12V, IP66

Waterproof IR Dome camera



ST ID57/O

- 1/3" SONY super HAD CCD
- Up to 650TVL/ 0 Lux IR ON
- IR distance: 15~20 meters
- 3.6 mm fixed lens
- OSD menu,DWDR,2D DNR,RS-485 (optional), MD,BLC,AGC
- DC 12V, IP66

Waterproof IR Dome camera